ERRATA SHEET

TENTATIVE ORDER NO. R9-2005-0136, NPDES NO. CA0107433

WASTE DISCHARGE REQUIREMENTS FOR THE CITY OF OCEANSIDE SAN LUIS REY AND LA SALINA WASTEWATER TREATMENT PLANTS AND BRACKISH GROUNDWATER DESALINATION FACILITY DISCHARGE TO THE PACIFIC OCEAN VIA THE OCEANSIDE OCEAN OUTFALL

Each of the following changes has been made to Tentative Order No. R9-2005-0136; NPDES No. CA0107433, in response to comments received to date. The changes/corrections are shown below in **bold and underline**/strikeout format to indicate added and removed language, respectively.

1. The dates in Table 3. Administrative Information on page 1 have been corrected:

This Order was adopted by the Regional Water Board on:	<u>August 10 June 8, 2005</u>						
This Order shall become effective on:	<u>August 10</u> June 8 , 2005						
This Order shall expire on:	<u>August 10</u> June 8, 2005						
The U.S. Environmental Protection Agency (U.S. EPA) and the Regional Water Board have classified this discharge as a major discharge.							
The Discharger shall file a Report of Waste Discharge in accordance with Title 2 not later than 180 days in advance of the Order expiration date as application for requirements.							

2. The following changes in the certification/adoption statement on page 1 has been made:

IT IS HEREBY ORDERED, that this Order supercedes Order No. 2000-011 except for enforcement purposes, and, in order to meet the provisions contained in Division 7 of the California Water Code (CWC) and regulations adopted thereunder, and the provisions of the federal Clean Water Act (CWA) and regulations and guidelines adopted thereunder, the Discharger shall comply with the requirements herein.

I, John H. Robertus, Executive Officer, do hereby certify that this Order with all attachments is a full, true, and correct copy of an Order adopted by the California Regional Water Quality Control Board, San Diego Region, on <u>August 10 June 8</u>, 2005.

3. The following Table of Contents replaces the Table of Contents on pages 2 and 3:

TABLE OF CONTENTS

<u>I.</u>	Facility Information	4
II.	Findings	5
III.	Discharge Prohibitions	8
	Discharge Specifications and Effluent Limitations	
	A. Discharge Specifications	10

B. Effluent Limitations and Performance Goals	11
V. Receiving Water Limitations	
A. Bacterial Characteristics	16
B. Physical Characteristics	16
C. Chemical Characteristics	17
D. Biological Characteristics	17
E. Radioactivity	17
VI. Provisions	17
A. Standard Provisions	
B. Monitoring and Reporting Program Requirements	20
C. Special Provisions	
VII. Compliance Determination	28
A. Average Monthly Effluent Limitation (AMEL)	28
B. Average Weekly Effluent Limitation (AWEL)	
C. Maximum Daily Effluent Limitation (MDEL)	
D. Instantaneous Minimum Effluent Limitation	
E. Instantaneous Maximum Effluent Limitation	
F. Six-month Median Effluent Limitation	
G. Mass and Concentration Limitations	
H. Percent Removal	29
I. Ocean Plan Provisions for Table B Constituents	
J. Receiving Water Sampling Protocol	32
K. Acute Toxicity	
L. Chronic Toxicity	
M. Toxicity Reduction Evaluation (TRE)	
N. Discharges to Surface Water	
O. Discharges to Land	34
P. Mass Emission Rate (MER)	34
Q. Bacterial Standards and Analysis	
R. Single Operational Upset	
Endnotes	
Enchoves	
LIST OF TABLES	
<u> </u>	
Table 1. Discharger Information	1
Table 2. Outfall Location	1
Table 3. Administrative Information	1
Table 4. Facility Information	4
Table 5. Basin Plan Beneficial Uses of the Pacific Ocean	6
Table 6. Ocean Plan Beneficial Uses of the Pacific Ocean	7
Table 7. Effluent Limitations	11
Table 7. Effluent Limitations Table 8. Performance Goals	14
<u>LIST OF ATTACHMENTS</u>	
Adda alamand A. Daffinidiana	1 · 4
Attachment A – Definitions	A-1
Attachment B – Map	B-1
Attachment C – Flow Schematic	C-1
Attachment D – Federal Standard Provisions	

ttachment E – Monitoring and Reporting Program (MRP) E-	1
ttachment F – Fact SheetF-	1
ttachment G – Diluton Model InformationG-	1

4. The following corrections have been made to Table 4 under Section I. Facility Information on page 4:

Table 4. Facility Information

Discharger	City of Oceanside
Name of Facility	Oceanside Ocean Outfall
	1330 South Tait Street
Facility Address	Oceanside, CA 92054
	San Diego County
Facility Contact, Title, and Phone	Barry E. Martin, Water Utilities Director, (760) 966-4850-435-5810
	1330 South Tait Street 300 North Coast Highway
Mailing Address	Oceanside, CA 92054
	San Diego County
Type of Facility	Municipal POTW
Facility Design Flow	22.9 million gallons per day (MGD)

5. The following corrections have been made to two sentences under Section II.B Facility Description on page 8:

Screenings from the headworks and solids from grit removal are trucked to a local landfill <u>or an</u> **Arizona landfill**.

The Discharger also operates the Brackish Groundwater Desalination Facility (BGDF) which produces up to 3 6 MGD of final potable water and 0.8 2 MGD waste brine.

6. The following correction to Section II.H *Water Quality Control Plans* on page 6 has been made:

The State Water Board adopted a *Water Quality Control Plan for Control of Temperature in the Coastal and Interstate Water and Enclosed Bays and Estuaries of California* (Thermal Plan) on May 18, 1972, and amended it this plan on September 18, 1975. The Thermal plan contains temperature objectives for coastal waters.

- 7. The following addition to Section III *Discharge Prohibitions* on page 9 has been made:

 <u>G. Compliance with Discharge Prohibitions contained in Section III.H of the Ocean Plan</u>
 is a requirement of this Order.
- 8. The following corrections have been made to Table 7b. Effluent Limitations based on California Ocean Plan 2001 in Section IV.B *Effluent Limitations and Performance Goals* on page 12:

Table 7b. Effluent Limitations based on California Ocean Plan 2001

		Effluent Limitations								
Constituent	Units	Max	Average	Average	Instar	ntaneous	6 Month			
		Daily	Monthly	Weekly	Min	Max	Median			
Oil and Grease	mg/l		25	40		75				
On and Grease	lbs/day		4.4 E+3	7.0 E+3		1.4 E+ <mark>34</mark>				
Settleable Solids	ml/l		1.0	1.5		3.0				
Turbidity	NTU		75	100		225				
Total Chlorine Residual ³	ug/l	7.0 E+02				5.3 E+03	1.8 E+02			
Total Chlorine Residual	lbs/day	1.3 E+02				1.0 E+03	3.4 E+01			
Ammonia (expressed as	ug/l	2.1 E+05				5.3 E+05	5.3 E+04			
nitrogen)	lbs/day	4.0 E+04				1.0 E+05	1.0 E+04			
Acute Toxicity	TUa	2.9 E+00								
Chronic Toxicity ⁴	TUc	8.8 E+01								
Phenolic Compounds	ug/l	1.1 E+04				2.6 E+04	2.6 E+03			
(non-chlorinated)	lbs/day	2.0 E+03				5.0 E+03	5.0 E+02			
Chlorinated Phenolics	ug/l	3.5 E+02				8.8 E+02	8.8 E+01			
Chiorinated Phenonics	lbs/day	6.7 E+01				1.7 E+02	1.7 E+01			
Endosulfan	ug/l	1.6 E+00				2.4 E+00	7.9 E-01			
Endosunan	lbs/day	3.0 E-01				4.5 E-01	1.5 E-01			
HCH ⁵	ug/l	7.0 E-01				1.1 E+00	3.5 E-01			
псп	lbs/day	1.3 E-01				2.0 E-01	6.7 E-02			
Acrolein	ug/l		1.9 E+04							
ACTOICHI	lbs/day		3.7 E+03							
Antimony	ug/l		1.1 E+05							
Anumony	lbs/day		2.0 E+04							
Bis(2-chloroethoxy)	ug/l		3.9 E+02							
Methane	lbs/day		7.4 E+01							
Bis(2-chloroisopropyl)	ug/l		1.1 E+05							
ether	lbs/day		2.0 E+04							
Chlorobenzene	ug/l		5.0 E+04							
Cinorobenzene	lbs/day		9.6 E+03							
Dichlorobenzenes 7	ug/l		4.5 E+05							
Dictitor obelizenes	lbs/day		8.6 E+04							
Ethylbenzene	ug/l		3.6 E+05							
<u> </u>	lbs/day		6.9 E+04							
Fluoranthene	ug/l		1.3 E+03							
r nuor ammente	lbs/day		2.5 E+02							
Thallium	ug/l		1.8 E+02							
-1 mainum	lbs/day		3.4 E+01							

		Effluent Limitations						
Constituent	Units	Max	Average	Average	Instantaneous		6 Month	
		Daily	Monthly	Weekly	Min	Max	Median	
Toluene	ug/l		7.5 E+06					
Totalic	lbs/day		1.4 E+06					
Tributyltin	ug/l		1.2 E-01					
	lbs/day		2.4 E-02					
1,1,1-trichloroethane	ug/l		4.8 E+07					
1,1,1-tricinor octilanc	lbs/day		9.1 E+06					
Aerylonitrile	ug/l		8.8 E+00					
reci yiomerne	lbs/day		1.7 E+00					
Aldrin	ug/l		1.9 E-03					
- Aldrin	lbs/day		3.7 E-04					
Benzene	ug/l		5.2 E+02					
Delizelle	lbs/day		9.9 E+01					
Benzidine	ug/l		6.1 E-03					
Denziume	lbs/day		1.2 E-03					
Downline	ug/l		2.9 E+00					
Beryllium	lbs/day		5.5 E-01					
Bis(2-chloroethyl)	ug/l		4.0 E+00					
Ether	lbs/day		7.6 E-01					
Bis(2-ethlyhexyl)	ug/l		3.1 E+02					
Phthalate	lbs/day		5.9 E+01					
G 1	ug/l		7.9 E+01					
Carbon Tetrachloride	lbs/day		1.5 E+01					
Chlordane 8	ug/l		2.0 E-03					
Chlordane	lbs/day		3.9 E-04					
CT 1 A	ug/l		1.1 E+04					
Chloroform	lbs/day		2.2 E+03					
DDT 0	ug/l		1.5 E-02					
DDT 9	lbs/day		2.9 E-03					
4.4.11.11	ug/l		1.6-E+03					
1,4-dichlorobenzene	lbs/day		3.0 E+02					
	ug/l		7.1 E-01					
3,3'-dichlorobenzidine	lbs/day		1.4 E-01					
	ug/l		2.5 E+03					
1,2-dichloroethane	lbs/day		4.7 E+02					
	ug/l		7.9 E+01					
1,1-dichloroethylene	lbs/day		1.5 E+01					
	ug/l		4.0 E+04					
Dichloromethane	lbs/day		7.6 E+03					
	ug/l		7.8 E+02					
1,3-dichloropropene	lbs/day		1.5 E+02					

				Effluent L	imitations			
Constituent	Units	Max	Average	Average	Instantaneous		6 Month	
		Daily	Monthly	Weekly	Min	Max	Median	
Dieldrin	ug/l		3.5 E-03					
Dictaria	lbs/day		6.7 E-04					
Halomethanes 10	ug/l		1.1 E+04					
Halomethanes	lbs/day		2.2 E+03					
Heptachlor	ug/l		4.4 E-03					
Першенног	lbs/day		8.4 E-04					
Hexachlorobenzene	ug/l		1.8 E-02					
Heademoropenzene	lbs/day		3.5 E-03					
PAHs ¹¹	ug/l		7.7 E-01					
	lbs/day		1.5 E-01					
PCBs 12	ug/l		1.7 E-03					
T CD5	lbs/day		3.2 E-04					
TCDD equivalents 13	ug/l		3.4 E-07					
1 CDD equivalents	lbs/day		6.6 E-08					
1,1,2,2-	ug/l		2.0 E+02					
tetrachloroethane	lbs/day		3.9 E+01					
Tetrachloroethylene	ug/l		1.8 E+02					
Tetraemoroconytene	lbs/day		3.4 E+01					
Toxaphene	ug/l		1.8 E-02					
Тохарисис	lbs/day		3.5 E-03					
Trichloroethylene	ug/l		2.4 E+03					
Tremoroctnyiche	lbs/day		4.5 E+02					
1,1,2-trichloroethane	ug/l		8.3 E+02					
1,1,2-trichloroethane	lbs/day		1.6 E+02					
Vinyl Chlorida	ug/l		3.2 E+03					
Vinyl Chloride	lbs/day		6.1 E+02					

- 9. The following corrections have been made to Table 8. Performance Goals based on California Ocean Plan 2001 and the accompanying narrative in Section B.3 *Effluent Limitations and Performance Goals* on page 14:
 - 3. Constituents that do not have reasonable <u>potential or had inconclusive reasonable</u> <u>potential analysis results</u> are referred to as performance goal constituents and assigned the performance goals listed in the following table. Performance goal constituents shall also be monitored at M-003, but the results will be used for informational purposes only, not compliance determination.

Table 8. Performance Goals based on California Ocean Plan 2001

		Goals based on California Ocean Plan 2001 Performance Goals									
Constituent	Units	Max	Avg Avg		Instar	Instantaneous					
		Daily	Monthly	Weekly	Min	Max	Median				
Arsenic	ug/l	2.6 E+03				6.8 E+03	4.4 E+02				
Aiscine	lbs/day	4.9 E+02				1.3 E+03	8.5 E+01				
Cadmium	ug/l	3.5 E+02				8.8 E+02	8.8 E+01				
Cuamum	lbs/day	6.7 E+01				1.7 E+02	1.7 E+01				
Chromium VI 1	ug/l	7.0 E+02				1.8 E+03	1.8 E+02				
	lbs/day	1.3 E+02				3.4 E+02	3.4 E+01				
Copper	ug/l	8.8 E+02				2.5 E+03	9.0 E+01				
Соррег	lbs/day	1.7 E+02				4.7 E+02	1.7 E+01				
Lead	ug/l	7.0 E+02				1.8 E+03	1.8 E+02				
Loud	lbs/day	1.3 E+02				3.4 E+02	3.4 E+01				
Mercury	ug/l	1.4 E+01				3.5 E+01	3.5 E+00				
TVICICUI y	lbs/day	2.7 E+00				6.7 E+00	6.6 E-01				
Nickel	ug/l	1.8 E+03				4.4 E+03	4.4 E+02				
NICKEI	lbs/day	3.4 E+02				8.4 E+02	8.4 E+01				
Selenium	ug/l	5.3 E+03				1.3 E+04	1.3 E+03				
Selemum	lbs/day	1.0 E+03				2.5 E+03	2.5 E+02				
Silver	ug/l	2.3 E+02				6.0 E+02	4.8 E+01				
Silvei	lbs/day	4.4 E+01				1.1 E+02	9.1 E+00				
Zinc	ug/l	6.3 E+03				1.7 E+04	1.1 E+03				
Zinc	lbs/day	1.2 E+03				3.2 E+03	2.0 E+02				
Cyanide ²	ug/l	3.5 E+02				8.8 E+02	8.8 E+01				
Cyamue	lbs/day	6.7 E+01				1.7 E+02	1.7 E+01				
Endrin	ug/l	3.5 E-01				5.3 E-01	1.8 E-01				
Endin	lbs/day	6.7 E-02				1.0 E-01	3.4 E-02				
Radioactivity ⁶				n 30253, St		7 California or Protection					
Acrolein	ug/l		1.9 E+04								
Actolem	<u>lbs/day</u>		3.7 E+03								
Antimony	ug/l		1.1 E+05								
Anumony	<u>lbs/day</u>		2.0 E+04								
Bis(2-chloroethoxy)	ug/l		3.9 E+02								
<u>Methane</u>	<u>lbs/day</u>		7.4 E+01								
Bis(2-chloroisopropyl)	ug/l		1.1 E+05								
ether	<u>lbs/day</u>		2.0 E+04								
Chlorobonzono	ug/l		5.0 E+04								
<u>Chlorobenzene</u>	lbs/day		9.6 E+03								
Chromium (III)	ug/l		1.7 E+07								
Cinomium (III)	lbs/day		3.2 E+06								

				Performa	nce Goals			
Constituent	Units	Max	Avg	Avg	Instantaneous		6 Month	
		Daily	Monthly	Weekly	Min	Max	Median	
Di-n-butyl Phthalate	ug/l		3.1 E+05					
Di-ii-outyi i iitiiaiate	lbs/day		5.9 E+04					
Dichlorobenzenes ⁷	ug/l		4.5 E+05					
<u>Dictior obelizenes</u>	<u>lbs/day</u>		8.6 E+04					
Diethyl Phthalate	ug/l		2.9 E+06					
Dietilyi Filmalate	lbs/day		5.5 E+05					
Dimethyl Phthalate	ug/l		7.2 E+07					
Difficulty Fittialate	lbs/day		1.4 E+07					
4,6-dinitro-2-	ug/l		1.9 E+04					
methylphenol	lbs/day		3.7 E+03					
2,4-dinitrophenol	ug/l		3.5 E+0 <mark>32</mark>					
2,4-diffitiophenoi	lbs/day		6.7 E+0 <mark>21</mark>					
E4b-ub on mone	ug/l		3.6 E+05					
Ethylbenzene	lbs/day		6.9 E+04					
Hexachlorocyclo-	ug/l		5.1 E+03					
pentadiene	lbs/day		9.7 E+02					
NT: 1	ug/l		4.3 E+02					
Nitrobenzene	lbs/day		8.2 E+01					
<u>Thallium</u>	ug/l		1.8 E+02					
	lbs/day		3.4 E+01					
	ug/l		7.5 E+06					
Toluene	lbs/day		1.4 E+06					
444411	ug/l		4.8 E+07					
1,1,1-trichloroethane	lbs/day		9.1 E+06					
	ug/l		8.8 E+00					
Acrylonitrile	lbs/day		1.7 E+00					
	ug/l		1.9 E-03					
<u>Aldrin</u>	lbs/day		3.7 E-04					
_	ug/l		5.2 E+02					
<u>Benzene</u>	lbs/day		9.9 E+01					
	ug/l		6.1 E-03					
Benzidine	lbs/day		1.2 E-03					
	ug/l		2.9 E+00					
<u>Beryllium</u>	lbs/day		5.5 E-01					
Bis(2-chloroethyl)	ug/l		4.0 E+00					
Ether	lbs/day		7.6 E-01					
Bis(2-ethlyhexyl)	ug/l		3.1 E+02					
Phthalate	lbs/day		5.9 E+01					
	ug/l		7.9 E+01					
Carbon Tetrachloride	lbs/day		1.5 E+01					

		Performance Goals							
Constituent	Units	Max Avg Avg Inst			taneous	6 Month			
		Daily	Monthly	Weekly	Min	Max	Median		
Chlordane 8	ug/l		2.0 E-03						
Chloruanc	<u>lbs/day</u>		3.9 E-04						
Chlorodibromomethane	ug/l		7.6 E+02						
Cinorodioro	lbs/day		1.4 E+02						
Chloroform	ug/l		1.1 E+04						
<u>Cinorotorini</u>	<u>lbs/day</u>		2.2 E+03						
DDT 9	ug/l		<u>1.5 E-02</u>						
<u>DD1</u>	<u>lbs/day</u>		2.9 E-03						
1,4-dichlorobenzene	ug/l		1.6 E+03						
1,4-dicinor obclizenc	<u>lbs/day</u>		3.0 E+02						
3,3'-dichlorobenzidine	ug/l		<u>7.1 E-01</u>						
5,5 -dicinoi obclizidine	<u>lbs/day</u>		<u>1.4 E-01</u>						
1,2-dichloroethane	ug/l		2.5 E+03						
1,2-uiciioi octifane	lbs/day		4.7 E+02						
1,1-dichloroethylene	ug/l		7.9 E+01						
1,1-dictior detriylene	lbs/day		1.5 E+01						
Dichlorobromomethane	ug/l		5.5 E+02						
Dicinorobromomeurane	lbs/day		1.0 E+02						
Dichloromethane	ug/l		4.0 E+04						
Dictioromethane	lbs/day		7.6 E+03						
1,3-dichloropropene	ug/l		7.8 E+02						
1,3-dichioropropene	lbs/day		1.5 E+02						
Dieldrin	ug/l		3.5 E-03						
<u>Dicium</u>	lbs/day		6.7 E-04						
2,4-dinitrotoluene	ug/l		2.3 E+02						
2,4-dillitrotoruelle	lbs/day		4.4 E+01						
1,2-diphenylhydrazine	ug/l		1.4 E+01						
1,2-diphenymydrazme	lbs/day		2.7 E+00						
Halomethanes 10	ug/l		1.1 E+04						
Halomethanes —	lbs/day		2.2 E+03						
Hentochlon	ug/l		4.4 E-03						
Heptachlor	lbs/day		8.4 E-04						
Heptachlor Epoxide	ug/l		1.8 E-03						
перисто прохие	lbs/day		3.4 E-04						
Hexachlorobenzene	ug/l		1.8 E-02						
11exacmoi obenzene	lbs/day		3.5 E-03						
Hexachlorobutadiene	ug/l		1.2 E+03						
пехасшогооциашене	lbs/day		2.4 E+02						
Hexachloroethane	ug/l		2.2 E+02						
110Ademoroculane	lbs/day		4.2 E+01						

				Performa	nce Goals			
Constituent	Units	Max	Avg	Avg	Instantaneous		6 Month	
		Daily	Monthly	Weekly	Min	Max	Median	
Isophorone	ug/l		6.4 E+04					
isophorone	lbs/day		1.2 E+04					
N-nitrosodimethylamine	ug/l		6.4 E+02					
N-muosounnemylanime	lbs/day		1.2 E+02					
N-nitrosodi-N-	ug/l		3.3 E+01					
propylamine	lbs/day		6.4 E+00					
N-nitrosodiphenylamine	ug/l		2.2 E+02					
N-muosodiphenylanine	lbs/day		4.2 E+01					
PAHs 11	ug/l		7.7 E-01					
<u>PAHS</u>	lbs/day		1.5 E-01					
PCBs 12	ug/l		1.7 E-03					
PCBS	lbs/day		3.2 E-04					
TCDD equivalents ¹³	ug/l		3.4 E-07					
1 CDD equivalents	<u>lbs/day</u>		<u>6.6 E-08</u>					
1,1,2,2-	ug/l		2.0 E+02					
tetrachloroethane	<u>lbs/day</u>		3.9 E+01					
Tetrachloroethylene	ug/l		1.8 E+02					
1 ett acmoi oetnytene	<u>lbs/day</u>		3.4 E+01					
Toxaphene	ug/l		1.8 E-02					
Тохариене	<u>lbs/day</u>		3.5 E-03					
Trichloroethylene	ug/l		2.4 E+03					
Tremoroemyiene	<u>lbs/day</u>		4.5 E+02					
1,1,2-trichloroethane	ug/l		8.3 E+02					
1,1,2°ti ichioi oethane	<u>lbs/day</u>		1.6 E+02					
2,4,6-trichlorophenol	ug/l		2.6 E+01					
2, 4 ,0-ti iciliorophellor	lbs/day		4.9 E+00					
Vinyl Chloride	ug/l		3.2 E+03					
v myr Chloride	<u>lbs/day</u>		6.1 E+02					

10. The following corrections to Section VI.A.2.g on page 19 has been made:

This Order expires on June 8 August 10, 2010, after which, the terms and conditions of this permit are automatically continued pending issuance of a new permit, provided that all requirements of USEPA's NPDES regulations at 40 CFR 122.6 and the State's regulations at CCR Title 23, Section 2235.4 regarding the continuation of expired permits and waste discharge requirements are met.

- 11. The following addition to Section VI *Provisions, C. Special Provisions* which begins on page 20 has been made:
 - 3. Planned Bypasses at La Salina Wastewater Treatment Plant

A bypass of the south treatment train at the La Salina Wastewater Treatment Plant for planned repair, maintenance and upgrades is not prohibited provided that all of the following are satisfied:

- a. At least three months prior to initiating a bypass, the discharger submits a technical report for the proposed bypass that includes the following:
 - (i) Start date and duration of the proposed bypass.
 - (ii) Scope of the proposed project.
 - (iii) Adequate information to demonstrate that the bypass is not a prohibited bypass because it meets the criteria given in Provision I.G.3 (a) and (b) of Attachment D Standard Provisions Permit Compliance.
 - (iv) Adequate information to demonstrate that the discharger has minimized the anticipated duration and anticipated impact of the proposed bypass.
- b. The Regional Board has provided the Discharger with written notification that the proposed bypass is not prohibited prior to initiating the bypass.
- c. For the duration of the bypass, the combined effluent at Monitoring Point M-003 is monitored at the same frequency as Monitoring Points M-001 and M-002 for the constituents listed under Monitoring and Reporting Program Table 3a and the combined effluent complies with the technology-based effluent limitations contained in Table 7a of Section IV. Discharge Specifications and Effluent Limitations of the Order. Determination of percent removal for carbonaceous biochemical oxygen demand and total suspended solids shall be based on a system-wide basis in lieu of the formula provided under Section VII. Compliance Determination.
- d. The discharger conducts additional effluent and receiving water monitoring relevant to the proposed bypass required by the Regional Board.
- 12. The following corrections have been made to Section VI.C.2.a on page 21:
 - 2. Special Studies, Technical Reports, and Additional Monitoring Requirements
 - a. Oceanside Ocean Outfall Capacity

No later than 180 days prior to the Order's expiration date, the Discharger shall submit a written report to the Executive Officer regarding capacity of the Oceanside Ocean Outfall (OOO) that addresses satisfies the following items:

- 1) Most current report on The OOO capacity evaluation was conducted within 365 days of the expiration four and a half years after the adoption date of this Order (June 8, 2010).
- 2) The report includes Tthe Discharger's best estimate of when the average daily flow will equal or exceed the OOO capacity.
- 3) The report includes Tthe Discharger's intended schedule for studies, design, and other steps needed to provide additional capacity for the OOO and/or to control the flow rate before the flow rate is equal to the current outfall capacity.
- 4) The report includes Report on an evaluation of the physical condition of the OOO conducted within four and a half years after the adoption date of this Order.
- 5) The report must be signed and agreed upon by each of the parties discharging through the OOO.
- 13. The following correction have been made to the first sentence of the first paragraph of Section VI.C.2.b regarding Treatment Plant Capacity on page 21:
 - The Discharger shall submit a written report to the Executive Officer within 90 days after the monthly average influent flow rate equals or exceeds 75 percent of the design secondary treatment capacity (3.94 MGD) of the wastewater treatment and/or disposal facilities.
- 14. Section VI.C.2.c regarding Spill Prevention and Response Plans on page 21 has been deleted.
- 15. Section VI.C.2.d has been renumbered as Section VI.C.2.c. The first paragraph of this section has been replaced by the following:
 - For purposes of this section, a spill is a discharge of treated or untreated wastewater that occurs at or downstream of the SLRWTP or LSWTP headworks in violation of Discharge Prohibition A of this Order, or a discharge of other materials related to treatment and operations of the SLRWTP, LSWTP and BGDF that occurs anywhere throughout the collection and treatment system owned and/or operated by the Discharger. This section does not include sanitary sewer overflows reportable under separate waste discharge requirements. The Discharger shall report spills in accordance with the following procedures:
- **16.** A new Section VI.C.2.d regarding Sanitary Sewer Systems and Sanitary Sewer Overflow Reporting has been added as follows:
 - d. Sanitary Sewer Systems and Sanitary Sewer Overflow Reporting Requirements

NPDES NO. CA0107433

A sanitary sewer system is a wastewater collection system including sewers, pipes, pumps, or other conveyances which convey wastewater (e.g. domestic, commercial, and industrial wastewaters) to a wastewater treatment plant. A sanitary sewer system is part of the publicly owned treatment works, and all federal Standard Provisions of this Order apply to a sanitary sewer system. A sanitary sewer overflow is each instance of a discharge from a sanitary sewer system at any point upstream of the headworks of a wastewater treatment plant. Temporary storage and conveyance facilities (such as wet wells, impoundments, tanks, highlines, etc.) are part of the sanitary sewer system and are not sanitary sewer overflows provided that sewage from these facilities is not discharged to waters of the State.

The Discharger shall report sanitary sewer overflows from the sanitary sewer system owned and operated by the Discharger in accordance with Monitoring and Reporting Program No. 96-04, Sanitary Sewer Overflow Reporting Procedures for Sewage Collection Agencies, incorporated by reference into this Order.

- 17. Section VI.C.2.g regarding Urban Runoff Diversions on page 28 has been deleted.
- 18. The following corrections have been made to the first sentence under Compliance Determination Section VII.K on page 32:

Compliance with the Acute Toxicity limitation in the Final Effluent Limitations

Performance Goals for Outfall 001 (Section IV.B.13 of this Order) shall be determined using an established protocol, e.g., American Society for Testing Materials (ASTM), USEPA, American Public Health Association, or State Board.

19. The following corrections have been made to Compliance Determination Section VII.M Toxicity Reduction Evaluation (TRE) on page 33:

The Discharger shall develop a Toxicity Reduction Evaluation (TRE) workplan in accordance with the TRE procedures established by the USEPA in the following guidance manuals:

- 1. Generalized Methodology for Conducting Industrial Toxicity Reduction Evaluations (EPA/600/2-88/070).
- 2. Toxicity Identification Evaluation, Phase I (EPA/600/6-91/005F).
- 3. Methods for Aquatic Toxicity Identification Evaluations, Phase II (EPA/600/R-92/080).
- 4. Methods for Aquatic Toxicity Identification Evaluations, Phase III (EPA/600/R-92/081).

The Discharger shall submit the TRE workplan to the Regional Water Board within 180 days of the adoption of this Order. The TRE workplan shall be subject to the approval of the Regional Water Board and shall be modified as directed by the Regional Water Board.

If <u>a</u> toxicity effluent limitations or performance goals identified in Section IV.B.2 of this Order <u>are is</u> exceeded, then within 15 days of the exceedance, the Discharger shall <u>begin</u> conducting six additional toxicity tests over a 6-month (at least one sample per calendar month, for a total of two samples per calendar month) conduct chronic and acute toxicity tests monthly for a 6-month period and provide the results to the Regional Water Board. The additional monthly toxicity tests will be incorporated into the semiannual discharge monitoring reports submitted pursuant to <u>MRP No. R9-2005-0136</u>. Attachment E – Monitoring and Reporting Program.

If the additional monthly tests indicate that toxicity effluent limitations are being consistently violated (at least three exceedances out of the six tests), the Regional Water Board may recommend that the Discharger conduct a TRE and a Toxic Identification Evaluation (TIE), as identified in the approved TRE workplan.

Within fifteen 30 days of completion of the TRE/TIE, the Discharger shall submit the results of the TRE/TIE, including a summary of the findings, data generated, a list of corrective actions necessary to achieve consistent compliance with all the toxicity limitation of this Order and prevent recurrence of violations of those limitation, and a time schedule for implementation of such corrective actions. The corrective actions and time schedule shall be modified at the direction of the Executive Officer.

- 20. Compliance Determination Sections VII.N and VII.O on page 34 have been deleted and following sections have been renumbered accordingly.
- 21. The following correction has been made to Compliance Determination Section VII.Q.2, which has been renumbered as Compliance Determination Sections VII.O.2:

For all bacterial analyses, sample dilutions should be performed so the range of values extends from 2 to 16,000 MPN (most probable number). The detection methods used for each analysis shall be reported with the results of the analysis. Detection methods used for coliforms (total and fecal) shall be those presented in the most recent edition of Standard Methods for the Examination of Water and Wastewater listed in 40 CFR 136 or any improved method determined by the Regional Water Board (and approved by USEPA) to be appropriate. Detection methods used for enterococcus shall be those presented in USEPA publication USEPA 600/4-85/076, Test Methods for Escherichia coli and Enterococci in Water by Membrane Filter Procedure, listed under 40 CFR 136, and any other approved method approved by the Regional Water Board. Test Methods for Escherichia coli and Enterococci in Water by Membrane Filter Procedure or any improved method determined by the Regional Water Board to be appropriate.

22. A definition for "Surface Waters" has been added to Attachment A – Definitions as follows:

Surface Waters include navigable waters, rivers, streams (including ephemeral streams), lakes, playa lakes, natural ponds, bays, the Pacific Ocean, lagoons, estuaries, man-made canals, ditches, dry arroyos, mudflats, sandflats, wet meadows, wetlands, swamps, marshes, sloughs and water courses, and storm drains tributary to surface waters.

Surface Waters include waters of the United States as used in the federal Clean Water Act (see 40 CFR 122.2)

23. The following Table of Contents replaces the Table of Contents on page E-1 of Attachment E – Monitoring and Reporting Program:

<u>ATTACHMENT E – MONITORING AND REPORTING PROGRAM</u>

Table of Contents

I. General Monitoring Provisions	E-2
II. Monitoring Locations	E-3
III. Influent Monitoring Requirements	E-4
IV. Effluent Monitoring Requirements	E-4
V. Whole Effluent Toxicity Requirements	E-7
VI. Receiving Water Monitoring Requirements	E-9
A. Surf Zone Water Quality Monitoring	E-9
B. Near Shore Water Quality Monitoring	E-10
C. Off Shore Water Quality Monitoring	E-10
D. Benthic Monitoring	E-10
E. Additional Biological Monitoring	E-11
F. Solids Monitoring	E-12
G. Kelp Bed Monitoring	E-12
H. Intensive Monitoring	E-13
I. Plume Tracking Study	E-13
J. Determination of Compliance with Water Quality Objectives	E-13
K. Urban Runoff Diversions	E-14
VII. Reporting Requirements	E-14
A. General Monitoring and Reporting Requirements	E-14
B. Self Monitoring Reports	E-15
C. Discharge Monitoring Reports (DMRs)	E-17
Endnotes	E_18

List of Tables

Table 1.	Monitoring Station Locations	E	<u>]-</u> ;
Table 2.	Influent Monitoring	F	<u></u> ,

Table 3.	Effluent Monitoring	E-5
Table 4.	Whole Effluent Toxicity Testing	E-7
Table 5.	Approved Tests For Chronic Toxicity	E-8
Table 6.	Near Shore Water Quality Requirements	E-10
Table 7.	Off Shore Water Quality Requirements	E-10
Table 8.	Sediment Monitoring Requirements	E-11
Table 9.	Infauna Monitoring Requirements	E-11
Table 10	. Demersal Fish and Macroinvertebrates Monitoring Requirements	E-11
Table 11	. Reporting Schedule	E-15

24. The following corrections have been made to Table 1. Monitoring Station Locations on page E-3 of Appendix E: Monitoring and Reporting Program:

Table 1. Monitoring Station Locations

Discharge Point Name	Monitoring Location Name	Monitoring Location Description	
	M-INF1	At a location where all influent flows to SLRWTP are accounted for in monitoring events; upstream of any in-plant return flows; and where representative samples of influent can be collected.	
	M-INF2	At a location where all influent flows to LSWTP are accounted for in monitoring events; upstream of any in-plant return flows; and where representative samples of influent can be collected.	
	M-001	Downstream of any in-plant return flows at SLRWTP where representative samples of effluent treated solely at SLRWTP can be collected.	
	M-002	Downstream of any in-plant return flows where representative samples of effluent treated solely at LSWTP can be collected.	
Outfall 001	M-003	At a location where representative samples of commingled effluent from SLRWTP, LSWTP, and BGDF and Biogen IDEC Pharmaceuticals Corp. can be collected before combining with wastewaters from Fallbrook Public Utility District and US Marine Corp Base Camp Pendleton.	
		- Receiving Water Monitoring Stations -	
		- Surf Zone Monitoring Stations -	
	<u>S1</u>	Surf Zone; 5,500 ft south of the outfall	
	S2	Surf Zone; 2,500 ft south of the outfall	
	S3	Surf Zone; at the outfall	
	S4	Surf Zone; 2,000 ft north of the outfall	
	S5	Surf Zone; 5,800 ft north of the outfall	
	S6	Surf Zone; 8,000 ft south of the outfall To be determined at a later date	
	S 7	Surf Zone; 10,000 ft south of the outfall To be determined at a later date	
		- Near Shore Monitoring Stations -	
	<u>N1</u>	Opposite S1; at the 30 foot depth contour, MLLW	
	N2	Opposite S2; at the 30 foot depth contour, MLLW	
	N3	Opposite S3; at the 30 foot depth contour, MLLW	

ORDER NO. R9-2005-0136 NPDES NO. CA0107433

Discharge Point Name	Monitoring Location Name	Monitoring Location Description	
	N4	Opposite S4; at the 30 foot depth contour, MLLW	
	N5	Opposite S5; at the 30 foot depth contour, MLLW	
	N6	Opposite S6; at the 30 foot depth contour, MLLW To be determined at a later date	
	N7	Opposite S7; at the 30 foot depth contour, MLLW To be determined at a later date	
		- Offshore Monitoring Stations -	
	A1 – A4	At the corners of a 1,000 ft x 1,000 ft square having one side parallel to shore and the intersection of its diagonals at the seaward end of the outfall	
	A5	At the seaward end of the outfall	
	B1	One mile downcoast from the outfall, and over the same depth contour as Station A5	
	B2	One mile upcoast from the outfall, and over the same depth contour as Station A5	
		- Biological Transects -	
	ТО	At the 20, 40, 60, and 80 ft depth contours along the transect located 50 ft downcoast of and parallel to the outfall	
	T1	At the 20, 40, 60, and 80 ft depth contours along the transect located 1 mile downcoast of and parallel to the outfall	
	T2	At the 20, 40, 60, and 80 ft depth contours along the transect located 1.5 miles upcoast of and parallel to the outfall	

25. The following corrections have been made to Table 3a. Effluent Monitoring at M-001 and M-002 in Section IV. Effluent Monitoring Requirements on page E-5 of Attachment E - Monitoring and Reporting Program:

Table 3a. Effluent Monitoring at M-001 and M-002

table 3a. Efficient workforing at wi-vor and wi-voz				
Parameter	Units	Sample Type ¹	Minimum Sampling Frequency	
Flow ¹⁴	MGD	recorder / totalizer	continuous	
CBOD ₅	mg/L	24 hr composite	daily ²	
BOD ₅	mg/L	24 hr composite	monthly	
TSS	mg/L	24 hr composite	daily ²	
pH	pH Units	grab	daily ²	
Oil and Grease	mg/L	grab	monthly ³	
Settleable Solids	mL/L	grab	daily ²	

26. The following rows have been added to Table 3b. Effluent Monitoring at M-003 in Section IV. Effluent Monitoring Requirements on page E-5 of Attachment E - Monitoring and Reporting Program:

Table 3b. Effluent Monitoring at M-003

Parameter	Units	Sample Type ¹	Minimum Sampling Frequency
Flow 14	MGD	recorder / totalizer	<u>continuous</u>
Oil and Grease	mg/L	<u>grab</u>	monthly ³
Settleable Solids	mL/L	<u>grab</u>	<u>daily ²</u>

27. The following corrections have been made to Table 3b. Effluent Monitoring at M-003 in Section IV. Effluent Monitoring Requirements on page E-5 of Attachment E - Monitoring and Reporting Program:

Table 3b. Effluent Monitoring at M-003

Parameter	Units	Sample Type ¹	Minimum Sampling Frequency
antimony	μg/L	Grab 24 hr composite	semiannually ³

28. The following corrections have been made to Table 4. Whole Effluent Toxicity Testing in Section V. Whole Effluent Toxicity Monitoring Requirements on page E-7 of Attachment E - Monitoring and Reporting Program:

Table 4. Whole Effluent Toxicity Testing

Test	Unit	Sample	Minimum Test Frequency
Acute Toxicity	TUa	24-Hr. Composite	quarterly
			<u>semiannually</u>
Chronic Toxicity	TU_c	24-Hr. Composite	quarterly

29. The following has replaced Section VI.B *Near Shore Water Quality Monitoring* on page E-10 of Attachment E - Monitoring and Reporting Program:

1. Reduced Monitoring

If the Executive Officer determines that the effluent at all times complies with Section IV.B Effluent Limitations and Performance Goals of Order No. R9-2005-0136, only reduced near shore water quality monitoring specified below is required.

Table 6. Near Shore Water Quality Reduced Monitoring Requirements

Determination	<u>Units</u>	Type of Sample	Minimum Frequency
Visual Observations	-1	=	<u>monthly</u>
Total and Fecal Coliform	<u>number / 100 ml</u>	grab ⁹	<u>monthly</u>
Enteroccoccus 5	<u>number / 100 ml</u>	grab ⁹	<u>monthly</u>

2. <u>Intensive Monitoring</u>

The intensive near shore water quality monitoring specified below is required during the 12-month period beginning July 1, 2008 through June 30, 2009, and must be submitted by August 31, 2009. This monitoring data will assist Regional board staff in the evaluation of the Report of Waste Discharge. The intensive near shore water quality monitoring specified below is also required if the Executive Officer determines that the effluent does not at all times comply with Section IV.B Effluent Limitations and Performance Goals of Order No. R9-2005-0136.

Table 7. Near Shore Water Quality Intensive Monitoring Requirements

Determination	<u>Units</u>	Type of Sample	<u>Minimum</u> <u>Frequency</u>
Visual Observations	<u>=</u>	<u>=</u>	monthly
Total and Fecal Coliform	<u>number / 100 ml</u>	grab ¹¹	<u>monthly</u>
Enteroccoccus ⁵	<u>number / 100 ml</u>	grab ¹¹	monthly

30. The following changes to Section VI.C *Off Shore Water Quality Monitoring* on page E-10 of Attachment E – Monitoring and Reporting Program has been made:

1. Reduced Monitoring

If the Executive Officer determines that the effluent at all times complies with Section IV.B Effluent Limitations and Performance Goals of Order No. R9-2005-0136, only reduced off shore water quality monitoring specified below is required.

Table 8. Off Shore Water Quality Reduced Monitoring Requirements

Determination	<u>Units</u>	Cype of Sample	<u>Minimum</u> <u>Frequency</u>
Visual Observations	<u>=</u>	<u>=</u>	monthly
Total and Fecal Coliform	<u>number / 100 ml</u>	grab ¹¹	<u>monthly</u>
Enteroccoccus 5	<u>number / 100 ml</u>	grab ¹¹	monthly

2. Intensive Monitoring

The intensive off shore water quality monitoring specified below is required during the 12-month period beginning July 1, 2008 through June 30, 2009, and must be submitted by August 31, 2009. This monitoring data will assist Regional board staff in the evaluation of the Report of Waste Discharge. The intensive off shore water quality monitoring specified below is also required if the Executive Officer determines that the effluent does not at all times comply with Section IV.B Effluent Limitations and Performance Goals of Order No. R9-2005-0136.

Table 9. Off Shore Water Quality Intensive Monitoring Requirements

Determination	<u>Units</u>	Units Type of Sample	
Visual Observations	-	-	<u>monthly</u>
Total and Fecal Coliform	<u>number / 100 ml</u>	grab 11	<u>monthly</u>
Enteroccoccus ⁵	<u>number / 100 ml</u>	grab ¹¹	<u>monthly</u>
Conductivity, Temperature and Depth (CTD)	Practical salinity units, ° C, feet	instrument (1- meter intervals, surface to bottom)	monthly
Dissolved Oxygen	mg/L	grab ¹²	<u>monthly</u>
Light Transmittance	<u>percent</u>	instrument 12	<u>monthly</u>
<u>pH</u>	<u>pH units</u>	grab ⁹	<u>monthly</u>

31. The following changes to Section VI.D *Benthic Monitoring* on pages E-10 and E-11 of Attachment E – Monitoring and Reporting Program have been made:

The monitoring specified below is required for a 12-month beginning July 1, 2008 through June 30, 2009. The monitoring data will assist Regional Water Board staff in the evaluation of the Report of Waste Discharge, which is required to be submitted by the Discharger within 180 days prior to the Order's expiration date of June 8, 2010. Benthic monitoring shall be conducted at all offshore monitoring stations.

The intensive monitoring specified below is required during the 12-month period beginning July 1, 2008 through June 30, 2009, and must be submitted by August 31, 2009. This monitoring data will assist Regional board staff in the evaluation of the Report of Waste Discharge. The sediment monitoring specified below is also required if the Executive Officer determines that the effluent does not at all times comply with Section IV.B Effluent Limitations and Performance Goals of Order No. R9-2005-0136. Benthic monitoring shall be conducted at all off shore monitoring stations.

1. <u>Sediment Characteristics</u>. Analyses shall be performed on the upper two inches of core.

Table 8. Sediment Monitoring Requirements

Determination	Units	Гуре of Sample	Minimum Frequency
Sulfides	mg/kg	core	Semi-annually Year 4
Total Chlorinated Hydrocarbons	mg/kg	core	Semi-annually Year 4
BOD ₅	mg/kg	core	Semi-annually Year 4
COD	mg/kg	core	Semi-annually Year 4
Particle Size Distribution	mg/kg	core	Semi-annually Year 4

Arsenic	mg/kg	core	Annually Year 4
Cadmium	mg/kg	core	Annually Year 4
Total Chromium	mg/kg	core	Annually Year 4
Copper	mg/kg	core	Annually Year 4
Lead	mg/kg	core	Annually Year 4
Mercury	mg/kg	core	Annually Year 4
Nickel	mg/kg	core	Annually Year 4
Silver	mg/kg	core	Annually Year 4
Zinc	mg/kg	core	Annually Year 4
Cyanide	mg/kg	core	Annually Year 4
Phenolic Compounds	mg/kg	core	Annually Year 4
Radioactivity	pCi/kg	core	Annually Year 4

2. <u>Infauna</u>. Samples shall be collected with a Paterson, Smith-McIntyre, or orange-peel type dredge, having an open sampling area of not less than 124 square inches and a sediment capacity of not less than 210 cubic inches. The sediment shall be sifted through a one-millimeter mesh screen and all organisms shall be identified to as low a taxon as possible.

Table 9 11. Infauna Monitoring Requirements

Determination	Units	Minimum Frequency
Benthic Biota	Identification and	3 grabs semi-annually Year 4
	enumeration	

- 32. The following correction has been made to the first paragraph under Section VI.H *Intensive Monitoring* on page E-13 of Attachment E–Monitoring and Reporting Program:

 The Discharger shall perform the intensive monitoring as described by this MRP for years 1 and 3 year 4 of the Order and participate in the Southern California Coastal Water Research Project (SCCWRP) Bight Study in year 5 of this Order.
- 33. Section VI.I *Plume Tracking Study* on page E-13 of Attachment E–Monitoring and Reporting Program has been deleted.

- 34. Section VI.J *Determination of Compliance with Water Quality Objectives* on page E-13 of Attachment E–Monitoring and Reporting Program has been deleted.
- 35. Section VI.K *Urban Runoff Diversions* on page E-13 of Attachment E–Monitoring and Reporting Program has been deleted.

The Discharger shall report all instances of noncompliance not reported under (Attachment **E-D**). III, **E-D**. VI, and **E-D**. VI of Order No. R9-2005-0136 at the time monitoring reports are submitted.

- 36. The following corrections have been made to Section VII.A.5 on page E-14 of Attachment E–Monitoring and Reporting Program:
- 37. The following correction has been made to Section VII.A.6 on page E-15 of Attachment E—Monitoring and Reporting Program:

Laboratory method detection limits (MDLs), practical quantitation limits (PQLs), and minimum Levels (MLs) shall be identified for each constituent in the matrix being analyzed with all reported analytical data. Acceptance of data shall be based on demonstrated laboratory performance.

38. The following Table of Contents replaces the Table of Contents on page F-1 of Attachment A-Fact Sheet:

<u>Attachment F – Fact Sheet</u>

Table of Contents

Permit Information	F-3
Facility Description	F-4
A. Description of Wastewater and Biosolids Treatment or Controls	F-4
B. Discharge Points and Receiving Waters	F-6
C. Summary of Existing Requirements and Self-Monitoring Report (SMR) Data	F-7
D. Compliance Summary	F-9
E. Planned Changes	F-9
Applicable Plans, Policies, and Regulations	F-10
A. Legal Authorities	F-10
B. California Environmental Quality Act (CEQA)	F-10
C. State and Federal Regulations, Policies, and Plans	F-10
D. Impaired Water Bodies on CWA 303(d) List	F-12
E. Other Plans, Policies, or Regulations	F-12
Rationale for Effluent Limitations and Discharge Specifications	F-13
A. Discharge Prohibitions	F-13
B. Technology-Based Effluent Limitations	F-13
C. Water Quality-Based Effluent Limitations (WQBELs)	F-15
D. Final Effluent Limitations	F-21
	Facility Description A. Description of Wastewater and Biosolids Treatment or Controls B. Discharge Points and Receiving Waters C. Summary of Existing Requirements and Self-Monitoring Report (SMR) Data D. Compliance Summary E. Planned Changes Applicable Plans, Policies, and Regulations A. Legal Authorities B. California Environmental Quality Act (CEQA) C. State and Federal Regulations, Policies, and Plans D. Impaired Water Bodies on CWA 303(d) List E. Other Plans, Policies, or Regulations Rationale for Effluent Limitations and Discharge Specifications A. Discharge Prohibitions B. Technology-Based Effluent Limitations C. Water Quality-Based Effluent Limitations (WQBELs)

	E.	Performance Goals	F-24
	F.		F-25
V.	Ration	ale for Receiving Water Limitationsl	F- 29
VI.		ale For Monitoring and Reporting Requirementsl	
	Α.	Influent Monitoringl	F- 29
	В.	Effluent Monitoringl	F- 29
	C.	Whole Effluent Toxicity Testing Requirements	F-30
	D.		F-30
	E.	Other Monitoring Requirements	F-32
VII.	Ration	nale for Provisions	F-35
	Α.	Standard Provisions	F -35
	В.	Special Provisions	F-35
VII	[. Public	Participationl	F -39
	Α.	Notification of Interested Parties	F -39
	В.	Written Comments	F -39
	C.	Public Hearingl	F -39
	D.	Waste Discharge Requirements Petition	F-40
	E.	Information and Copyingl	F-40
	F.	Register of Interested Persons	F-40
	G.	Additional Informationl	F-40

List of Tables

<u>Table 1.</u>	Facility Information	<u> F-3</u>
Table 2.	Historical Flows	F-6
	Discharges Through Oceanside Ocean Outfall	
Table 4.	Historic Effluent Limitations and Monitoring Data	F-7
Table 5.	Toxic Pollutant Monitoring	F-8
Table 6.	Basin Plan Beneficial Uses of the Pacific OceanFe	<u>-10</u>
	Ocean Plan Beneficial Uses of the Pacific Ocean	
Table 8.	Summary of Technology-Based Effluent Limitations for Secondary	
	Treatment Facilities Established by USEPA at 40 CFR 133.102	F-14
Table 9.	Summary of Technology-Based Effluent Limitations for POTWs	
	Established by the Ocean Plan (2001)	F-14
Table 10.	. Pollutants Having Background Concentrations	F-18
Table 11.	. Copper, Chronic Toxicity, Chloroform, and Chlorine	F-18
	. New Toxic Pollutants and Corresponding Limitations	
Table 13.	. Toxic Pollutant Effluent Limitations or Performance Goals	
	Based on the 2001 California Ocean Plan	F-20
	. Summary of Final Effluent Limitations	
Table 15.	. Performance Goals Based on the 2001 California Ocean Plan	F-24
	. Influent Monitoring Requirements	
	. Sediment Monitoring Requirements	
Table 18.	. Infauna Monitoring Requirements	F-33

39. The following correction to the third sentence of the fourth paragraph of Section II.A of the Fact Sheet on page F-4 has been corrected as follows:

The higher treatment capacity of SLRWTP resulting from the addition of the West Plant was approved by the Regional Water Board on May June 21, 2005.

40. The following corrections have been made to the second paragraph under Section II.B of the Fact Sheet on page F-6:

The design capacity of the OOO is 30 MGallons/Day (average daily flow), with a maximum rated peak-day capacity of 45 MGallons/Day. The Discharger is subject to a flow limitation of 22.9 MGD contained in this Order for the discharge of effluent from its Facilities through the OOO to the Pacific Ocean. The Discharger has a contract with the Fallbrook Public Utility District (FPUD) for the discharge of an average annual flowrate of 2.4 MGallons/Day of treated wastewater from the FPUD through the OOO, subject to waste discharge requirements contained in Order No. 2000-012 (NPDES No. CA0108031) which is scheduled for renewal on June 8, 2005 as Order No. R9-2005-0137. The City of Oceanside has a contract with the US Marine Corp Base Camp Pendleton (USMCBCP) for the discharge of up to 3.6 MGD of undisinfected secondary effluent, treated at USMCBCP Wastewater Treatment Plant Nos. 1, 2, 3, and 13, to the Pacific Ocean through the OOO, subject to waste discharge requirements contained in Order No. R9-2003-0155 (NPDES Permit No. CA0109347) which was adopted by the Regional Board on August 13, 2003. The City of Oceanside has a contract with Biogen IDEC Pharmaceuticals Corporation (IDEC) for the discharge of up to 0.155 MGD of brine and other wastes associated with water softening and purification processes and other non-industrial maintenance-type activities to the Pacific Ocean through the OOO, subject to waste discharge requirements contained in Order No. R9-2003-0140 (NPDES Permit No. CA0109193) which was adopted by the Regional Board on August 13, 2003. The Discharger allows the discharge from IDEC to commingle with its discharge prior to Outfall 001 Monitoring Station M-003 which could influence the Discharger's ability to comply effluent limitations. The combined permitted flowrate from all agencies discharging through the OOO is 29.055 MGD.

41. The following corrections were made to the first paragraph and Table 4 under Section II.C of the Fact Sheet on page F-7:

Effluent limitations contained in Order No. 2000-0121 for discharges from the Discharger's Facility and representative monitoring data obtained at Monitoring Locations M-001 and M-002 for years 1999 through 2003 are as follows:

Table 4. Historic Effluent Limitations and Monitoring Data

Parameter (units)		I	Effluent Limita	Monitoring Data (From 1999 To 2003)		
		Monthly Average (30-day)	Weekly Average (7-day)	Maximum at any time	Mean Discharge	Maximum Discharge
CBOD ₅	mg/L	25	40	45	5.8 <u>3.5</u>	220 - <u>23.2</u>
	lbs/day	4 10 - <u>3400</u>	650 - <u>5400</u>	730 - <u>6100</u>	72	2,766
TSS	mg/L	30	45	50	4 .7 <u>6.3</u>	430 - <u>146</u>
	lbs/day	4 90 -4100	730 - <u>6100</u>	810 <u>6800</u>	56	5,407
O&G	mg/L	25	40	75	5.3 - <u>10</u>	29 - <u>50</u>
	lbs/day	4 10 - <u>3400</u>	650 - <u>5400</u>	730 - <u>10000</u>	58.9	212
Settleable Solids	mL/L	1.0	1.5	3.0	0.1	0.1 - <u>42</u>
Turbidity	NTU	75	100	225	1.78 - <u>3.9</u>	11.5 - <u>75</u>
pН			6.0 to 9.0		7.14 <u>7.4</u>	7.48 <u>8.1</u>
Acute toxicity	TUa	1.5	2.0	2.5	0.61 - <u>1.1</u>	1.18 - <u>3.0</u>

42. The following corrections were made to the first sentence of the third paragraph under Section II.C of the Fact Sheet on page F-8:

The effluent exceeded technology-based acute toxicity effluent limits based on acute toxicity test results for samples taken on January 9, 2003 (1.56 TUa); March 21 and 28, 2003 (3.04 and 2.09 1.62 TUa); and April 8, 2003 (1.79 TUa).

43. The following corrections were made to Table 5 under Section II.C of the Fact Sheet on page F-8:

Table 5. Toxic Pollutant Monitoring

Toxic Pollutant from Table B of the Ocean Plan (1997)	Monitoring Frequency
Ammonia	Monthly
Chlorine	Daily
Metals, Cyanide, Chlorinated and Non-Chlorinated Phenolics, Endosulfan, Endrin, HCH, Radioactivity	
Table B pollutants listed with Objectives for the Protection of	Quarterly
Marine Aquatic Life from the Ocean Plan (1997) except	
ammonia, chlorine and chronic toxicity	
All other Table B pollutants from the Ocean Plan (1997)	Semi-Annually

44. The following is inserted as Section III.C.5 Alaska Rule on page F-12 of Attachment F:

Alaska Rule. On March 30, 2000, USEPA revised its regulation that specifies when new and revised State and Tribal water quality standards (WQS) become effective for Clean Water Act (CWA) purposes (40 CFR 131.21, 65 FR 24641, April 27, 2000). Under USEPA's new regulation (also known as the Alaska rule), new and revised

standards submitted to USEPA after May 30, 2000, must be approved before being used for CWA purposes. The final rule also provides that standards already in effect and submitted to USEPA by May 30, 2000, may be used for CWA purposes, whether or not approved by USEPA.

45. The following is inserted as Section III.C.6 *No More Stringent Than Federal Law* on page F-12 of Attachment F:

No More Stringent Than Federal Law. This Order contains restrictions on individual pollutants that are no more stringent than required by the federal Clean Water Act. Individual pollutant restrictions consist of technology-based restrictions and water quality-based effluent limitations. The technology-based effluent limitations consist of restrictions on carbonaceous biochemical oxygen demand (CBOD₅), total suspended solids (TSS), and hydrogen ion concentration (pH). Restrictions on CBOD5, TSS, and pH are specified in federal regulations as discussed in Finding F, and the Order's technology-based pollutant restrictions are no more stringent than required by the Clean Water Act. Water quality-based effluent limitations have been derived to implement water quality objectives that protect beneficial uses. Both the beneficial uses and the water quality objectives have been approved pursuant to federal law and are the applicable federal water quality standards. To the extent that toxic pollutant water quality-based effluent limitations were derived from the Ocean Plan (2001), the Ocean Plan is the applicable standard pursuant to CWA Section 303(c)(1). The scientific procedures for calculating the individual water quality-based effluent limitations are based on the Program of Implementation contained in the California Ocean Plan, which was adopted by the State Water Resources Control Board on November 16, 2000 and approved by USEPA on December 3, 2001. Most beneficial uses and water quality objectives contained in the Basin Plan were approved under state law and submitted to and approved by USEPA prior to May 30, 2000. Any water quality objectives and beneficial uses submitted to USEPA prior to May 30, 2000, but not approved by USEPA before that date, are nonetheless "applicable water quality standards for purposes of the [Clean Water] Act" pursuant to 40 CFR 131.21(c)(1). The remaining water quality objectives and beneficial uses implemented by this Order (specifically temperature) were adopted in the Water Quality Control Plan for Control of Temperature in the Coastal and Interstate Water and Enclosed Bays and Estuaries of California (Thermal Plan) on May 18, 1972 and amended on September 18, 1975 and are applicable water quality standards pursuant to 40 CFR 131.21(c)(1). Collectively, this Order's restrictions on individual pollutants are no more stringent than required to implement the technology-based requirements of the Clean Water Act and the applicable water quality standards for purposes of the Clean Water Act.

46. The following changes to Section IV.A *Discharge Prohibitions* on page F-11 of Attachment F have been made:

Prohibition A.1 of Order No. 2000-011 been modified to clearly define what types of discharges are prohibited by this Order. The modified prohibition is contained in Section III.A of this Order. In addition, language has been added in Section VII, Compliance Determination, which accurately describes how violations of Prohibition III.A and the other discharge prohibitions contained in Order No. R9-2005-0136 are determined. Discharges from the Facility to surface water in violation of prohibitions contained in Order No. R9-2005-01036 are violations of the Clean Water Act and therefore are subject to third party lawsuits. Discharges from the Facility to land in violation of prohibitions contained in Order No. R9-2005-0136 are violations of the California Water Code and are not subject to third party lawsuits under the Clean Water Act (the California Water Code does not contain provisions allowing third party lawsuits). This clarification is intended to address concerns raised by Dischargers regarding third party lawsuits.

47. The following corrections were made to the second paragraph under Section IV.C.3 of the Fact Sheet on page F-17:

Conventional pollutants were not a part of the reasonable potential analysis and are included in this Order as described in Section B.2 above. Constituents that did not have enough data to run an RPA have retained their effluent limitations from Order No. 2000-011. Effluent limitations from Order No. 2000-011 are not retained for constituents for which RPA results indicated Endpoint 3; performance goals have instead also been assigned for these constituents. The MRP for this Order is designed to obtain additional information for these constituents to determine if reasonable potential exists for these constituents in future permit renewals and/or updates.

48. The following correction was made to the second paragraph under Section IV.C.5 of the Fact Sheet on page F-20:

There is no requirement to monitor for acute toxicity for discharges with minimum initial dilution factors below 100; however, a requirement to monitor for acute toxicity semiannually is included to ensure that recent actions taken by the Discharger to control acute toxicity remain effective and to provide appropriate data for future RPA. However, bBased on a reasonable potential analysis result of Endpoint 2 using acute toxicity data from June 2003 through May 2005 and the Discharger's compliance history, a water quality-based acute toxicity performance goal of 2.91 TUa is included in Order No. R9-2005-0136 which replaces the technology-based acute toxicity effluent limitation in Order No. 2000-011.

49. The following corrections have been made to Table 7b. Effluent Limitations based on California Ocean Plan 2001 in Section IV.D Final Effluent Limitations on page F-21 of the Fact Sheet:

Table 7b. Effluent Limitations based on California Ocean Plan 2001

				Effluent L	imitations		
Constituent	Units	Max	Average	Average	Instan	ntaneous	6 Month
		Daily	Monthly	Weekly	Min	Max	Median
Oil and Grease	mg/l		25	40		75	
On and Orease	lbs/day		4.4 E+3	7.0 E+3		1.4 E+ <mark>34</mark>	
Settleable Solids	ml/l		1.0	1.5		3.0	
Turbidity	NTU		75	100		225	
Total Chlorine Residual ³	ug/l	7.0 E+02				5.3 E+03	1.8 E+02
Total Chlorine Residual	lbs/day	1.3 E+02				1.0 E+03	3.4 E+01
Ammonia (expressed as	ug/l	2.1 E+05				5.3 E+05	5.3 E+04
nitrogen)	lbs/day	4.0 E+04				1.0 E+05	1.0 E+04
Acute Toxicity	TUa	2.9 E+00					
Chronic Toxicity ⁴	TUc	8.8 E+01					
Phenolic Compounds	ug/l	1.1 E+04				2.6 E+04	2.6 E+03
(non-chlorinated)	lbs/day	2.0 E+03				5.0 E+03	5.0 E+02
Chlorinated Phenolics	ug/l	3.5 E+02				8.8 E+02	8.8 E+01
	lbs/day	6.7 E+01				1.7 E+02	1.7 E+01
Endosulfan	ug/l	1.6 E+00				2.4 E+00	7.9 E-01
	lbs/day	3.0 E-01				4.5 E-01	1.5 E-01
HCH ⁵	ug/l	7.0 E-01				1.1 E+00	3.5 E-01
псп	lbs/day	1.3 E-01				2.0 E-01	6.7 E-02
Acrolein	ug/l		1.9 E+04				
Herotetti	lbs/day		3.7 E+03				
Antimony	ug/l		1.1 E+05				
Anumony	lbs/day		2.0 E+04				
Bis(2-chloroethoxy)	ug/l		3.9 E+02				
Methane	lbs/day		7.4 E+01				
Bis(2-chloroisopropyl)	ug/l		1.1 E+05				
ether	lbs/day		2.0 E+04				
Chlorobenzene	ug/l		5.0 E+04				
	lbs/day		9.6 E+03				
Dichlorobenzenes 7	ug/l		4.5 E+05				
	lbs/day		8.6 E+04				
Ethylbenzene	ug/l		3.6 E+05				
	lbs/day		6.9 E+04				
Fluoranthene	ug/l		1.3 E+03				

				Effluent Li	imitations			
Constituent	Units	Max Average Average			Instan	Instantaneous		
		Daily	Monthly	Weekly	Min	Max	Median	
	lbs/day		2.5 E+02					
Thallium	ug/l		1.8 E+02					
Thamum	lbs/day		3.4 E+01					
Toluene Tributablia	ug/l		7.5 E+06					
	lbs/day		1.4 E+06					
Tributyltin	ug/l		1.2 E-01					
	lbs/day		2.4 E-02					
1,1,1-trichloroethane	ug/l		4.8 E+07					
1,1,1-tricinoroctilane	lbs/day		9.1 E+06					
Aerylonitrile	ug/l		8.8 E+00					
Actylometric	lbs/day		1.7 E+00					
Aldrin	ug/l		1.9 E-03					
	lbs/day		3.7 E-04					
Benzene	ug/l		5.2 E+02					
Denzene	lbs/day		9.9 E+01					
Benzidine	ug/l		6.1 E-03					
Denziume	lbs/day		1.2 E-03					
Beryllium	ug/l		2.9 E+00					
	lbs/day		5.5 E-01					
Bis(2-ehloroethyl)	ug/l		4.0 E+00					
Ether	lbs/day		7.6 E-01					
Bis(2-ethlyhexyl)	ug/l		3.1 E+02					
Phthalate	lbs/day		5.9 E+01					
Carbon Tetrachloride	ug/l		7.9 E+01					
Carbon Tetracmoriue	lbs/day		1.5 E+01					
Chlordane 8	ug/l		2.0 E-03					
Cinoruane	lbs/day		3.9 E-04					
Chloroform	ug/l		1.1 E+04					
Cinorotoria	lbs/day		2.2 E+03					
DDT-9	ug/l		1.5 E-02					
ייעע א	lbs/day		2.9 E-03					
1 4 diablambangana	ug/l		1.6 E+03					
1,4-dichlorobenzene	lbs/day		3.0 E+02					
3,3'-dichlorobenzidine	ug/l		7.1 E-01					
5,5 -uicinorobenziaine	lbs/day		1.4 E-01					
1,2-dichloroethane	ug/l		2.5 E+03					
1,2-uicmoroethane	lbs/day		4.7 E+02					
1.1 diablamath-lana	ug/l		7.9 E+01					
1,1-dichloroethylene	lbs/day		1.5 E+01					
Dichloromethane	ug/l		4.0 E+04					

ORDER NO. R9-2005-0136 NPDES NO. CA0107433

				Effluent L	imitations		
Constituent	Units	Max Average Average			taneous	6 Month	
		Daily	Monthly	Weekly	Min	Max	Median
	lbs/day		7.6 E+03				
1,3-dichloropropene	ug/l		7.8 E+02				
1,5-dicinor opropene	lbs/day		1.5 E+02				
Dieldrin	ug/l		3.5 E-03				
	lbs/day		6.7 E-04				
Halomethanes 10	ug/l		1.1 E+04				
Halomethanes	lbs/day		2.2 E+03				
Heptachlor	ug/l		4.4 E-03				
rieptacinor	lbs/day		8.4 E-04				
IIhlh	ug/l		1.8 E-02				
Hexachlorobenzene	lbs/day		3.5 E-03				
PAHs 11	ug/l		7.7 E-01				
PAHs."	lbs/day		1.5 E-01				
PCBs-12	ug/l		1.7 E-03				
PUBS	lbs/day		3.2 E-04				
TCDD 1 1 13	ug/l		3.4 E-07				
TCDD equivalents 13	lbs/day		6.6 E-08				
1,1,2,2-	ug/l		2.0 E+02				
tetrachloroethane	lbs/day		3.9 E+01				
T (11 (1 1	ug/l		1.8 E+02				
Tetrachloroethylene	lbs/day		3.4 E+01				
TD 1	ug/l		1.8 E-02				
Toxaphene	lbs/day		3.5 E-03				
	ug/l		2.4 E+03				
Trichloroethylene	lbs/day		4.5 E+02				
1.1.2 twishlows ath	ug/l		8.3 E+02				
1,1,2-trichloroethane	lbs/day		1.6 E+02				
Vinyl Chlorida	ug/l		3.2 E+03				
Vinyl Chloride	lbs/day		6.1 E+02				

50. The following corrections have been made to the paragraph above Table 8. Performance Goals based on California Ocean Plan 2001 in Section IV.E Performance Goals on page F-23 of the Fact Sheet and to above Table 8. Performance Goals based on California Ocean Plan 2001:

Constituents that do not have reasonable potential are listed as performance goals in this Order. The following tables lists the performance goals established by Order No. R9-2005-0136. These constituents shall also be monitored at M-001 M-003, but the results will be used for informational purposes only, not compliance determination. Mass emissions have

been derived based on a flow of 22.9 MGD, which is the combined design capacity of the Discharger's Facilities, and a minimum probable initial dilution factor of 87:1

Table 8. Performance Goals based on California Ocean Plan 2001

		Performance Goals					
Constituent	Units	Max	Avg	Avg	Instantaneous		6 Month
		Daily	Monthly	Weekly	Min	Max	Median
Arsenic	ug/l	2.6 E+03				6.8 E+03	4.4 E+02
Aiscilic	lbs/day	4.9 E+02				1.3 E+03	8.5 E+01
Cadmium	ug/l	3.5 E+02				8.8 E+02	8.8 E+01
Caumum	lbs/day	6.7 E+01				1.7 E+02	1.7 E+01
Chromium VI ¹	ug/l	7.0 E+02				1.8 E+03	1.8 E+02
Chromium VI	lbs/day	1.3 E+02				3.4 E+02	3.4 E+01
Copper	ug/l	8.8 E+02				2.5 E+03	9.0 E+01
Соррег	lbs/day	1.7 E+02				4.7 E+02	1.7 E+01
Lead	ug/l	7.0 E+02				1.8 E+03	1.8 E+02
Leau	lbs/day	1.3 E+02				3.4 E+02	3.4 E+01
Mercury	ug/l	1.4 E+01				3.5 E+01	3.5 E+00
Mercury	lbs/day	2.7 E+00				6.7 E+00	6.6 E-01
Nickel	ug/l	1.8 E+03				4.4 E+03	4.4 E+02
Nickei	lbs/day	3.4 E+02				8.4 E+02	8.4 E+01
Selenium	ug/l	5.3 E+03				1.3 E+04	1.3 E+03
	lbs/day	1.0 E+03				2.5 E+03	2.5 E+02
Silver	ug/l	2.3 E+02				6.0 E+02	4.8 E+01
Silver	lbs/day	4.4 E+01				1.1 E+02	9.1 E+00
Zinc	ug/l	6.3 E+03				1.7 E+04	1.1 E+03
Zinc	lbs/day	1.2 E+03				3.2 E+03	2.0 E+02
Cyanide ²	ug/l	3.5 E+02				8.8 E+02	8.8 E+01
Cyamac	lbs/day	6.7 E+01				1.7 E+02	1.7 E+01
Endrin	ug/l	3.5 E-01				5.3 E-01	1.8 E-01
Liidiiii	lbs/day	6.7 E-02				1.0 E-01	3.4 E-02
						7 California	
Radioactivity 6		Regulat	n Against				
		Radiation					
Acrolein	ug/l		1.9 E+04				
rerotem	<u>lbs/day</u>		3.7 E+03				
Antimony	ug/l		1.1 E+05				
	<u>lbs/day</u>		2.0 E+04				
Bis(2-chloroethoxy) Methane	ug/l		3.9 E+02				
	<u>lbs/day</u>		7.4 E+01				
$\underline{Bis(2\text{-}chloroisopropyl)}$	ug/l		1.1 E+05				
<u>ether</u>	<u>lbs/day</u>		2.0 E+04				
<u>Chlorobenzene</u>	ug/l		5.0 E+04				

Daily Monthly Weekly Min Max Med								
Ibs/day	Constituent	Units				·		6 Month
Chromium (III) ug/l 1.7 E+07 lbs/day 3.2 E+06			Daily		Weekly	Min	Max	Median
Dischorophyse Disc								
Di-n-butyl Phthalate ug/l 3.1 E+05	Chromium (III)	_						
Dichlorobenzenes 7		1						
Dichlorobenzenes Toluene Dichlorobenzenes Dichlorobenzenes Dichlorobenzenes Dichlorobenzenes Dichlorobenzenes Dichlorobenzenes Dichlorobenzenes Dichlorobenzenes Dichlorobenzenes Dichlorobenzene Dichloro	Di-n-butyl Phthalate	_						
Dichlorobenzeles Ibs/day S.6 E+04		1 1						
Diethyl Phthalate ug/l 2.9 E+06	Dichlorobenzenes 7							
Diethyl Phthalate Ibs/day 5.5 E+05		<u>lbs/day</u>						
Dimethyl Phthalate ug/l 7.2 E+07	Diethyl Phthalate	ug/l		2.9 E+06				
Dimethyl Prinalate Ibs/day 1.4 E+07		lbs/day		5.5 E+05				
1.4 E+07	Dimethyl Phthalate	ug/l		7.2 E+07				
methylphenol lbs/day 3.7 E+03 1 2,4-dinitrophenol ug/l 3.5 E+032 1 lbs/day 6.7 E+021 1 Ethylbenzene ug/l 3.6 E+05 1 lbs/day 6.9 E+04 1 Hexachlorocyclopentadiene lbs/day 9.7 E+02 1 Nitrobenzene ug/l 4.3 E+02 1 lbs/day 8.2 E+01 1 Thallium ug/l 1.8 E+02 1 lbs/day 3.4 E+01 1 Toluene ug/l 7.5 E+06 1 lbs/day 1.4 E+06 1 1.1.1-trichloroethane ug/l 4.8 E+07 1 lbs/day 9.1 E+06 1 Acrylonitrile lbs/day 1.7 E+00 1.7 E+00		lbs/day		1.4 E+07				
2,4-dinitrophenol ug/l 3.5 E+032		ug/l		1.9 E+04				
1bs/day 6.7 E+021	methylphenol	lbs/day		3.7 E+03				
Bbs/day 6.7 E+021	2.4 dinitrophenol	ug/l		3.5 E+0 <mark>32</mark>				
Hexachlorocyclopentadiene ug/l	2,4-diffitiophenoi	lbs/day		6.7 E+0 2<u>1</u>				
Hexachlorocyclo-pentadiene	Ethylhonzono	ug/l		3.6 E+05				
Desiration Des	Ethylbenzene	lbs/day		6.9 E+04				
Nitrobenzene ug/l	Hexachlorocyclo-	ug/l		5.1 E+03				
Thallium		lbs/day		9.7 E+02				
Thallium	Nitualian	ug/l		4.3 E+02				
Toluene	Nitrobenzene	lbs/day		8.2 E+01				
Toluene	Thelling	ug/l		1.8 E+02				
Toluene ug/l 7.5 E+06 9 lbs/day 1.4 E+06 9 1,1,1-trichloroethane ug/l 4.8 E+07 lbs/day 9.1 E+06 9 Acrylonitrile ug/l 8.8 E+00 lbs/day 1.7 E+00 9	<u>1 namum</u>	lbs/day		3.4 E+01				
1.4 E+06	Tolores			7.5 E+06				
1,1,1-trichloroethane ug/l 4.8 E+07 Bb/day 9.1 E+06 Acrylonitrile ug/l 8.8 E+00 Ibs/day 1.7 E+00	<u>1 oruene</u>	lbs/day						
1,1,1-tricnioroetnane	444411 4							
Acrylonitrile ug/l 8.8 E+00 lbs/day 1.7 E+00	1,1,1-trichloroethane							
lbs/day 1.7 E+00								
	<u>Acrylonitrile</u>							
ug/l 1.9 E-03	Alduin	ug/l		1.9 E-03				
Aldrin lbs/day 3.7 E-04	<u>Aldrin</u>							
11g/l 5 2 F+02	<u>Benzene</u>							
Benzene Benzene P.9 E+01 P.								
ng/l 61F-03	<u>Benzidine</u>							
Benzidine lbs/day 1.2 E-03								
19g/l 2.9 F±00								
Beryllium lbs/day 5.5 E-01	Beryllium							
Bis(2-chloroethyl) ug/l 4.0 E+00	Bis(2-chloroethyl)							
Ether lbs/day 7.6 E-01								
Bis(2-ethlyhexyl) ug/l 3.1 E+02								

				Performance Goals			
Constituent	Units	Max	Avg	Avg	Instantaneous		6 Month
		Daily	Monthly	Weekly	Min	Max	Median
<u>Phthalate</u>	<u>lbs/day</u>		<u>5.9 E+01</u>				
Carbon Tetrachloride	ug/l		7.9 E+01				
Carbon Tetraemoriue	<u>lbs/day</u>		<u>1.5 E+01</u>				
Chlordane 8	ug/l		<u>2.0 E-03</u>				
Ciliordane	<u>lbs/day</u>		3.9 E-04				
Chlorodibromethane	ug/l		7.6 E+02				
Chlorodioromethane	lbs/day		1.4 E+02				
Chloroform	ug/l		1.1 E+04				
CIIIOTOTOTIII	lbs/day		2.2 E+03				
DDT 9	ug/l		1.5 E-02				
<u>DD1</u>	lbs/day		2.9 E-03				
1,4-dichlorobenzene	ug/l		1.6 E+03				
1,4-dichiorobenzene	lbs/day		3.0 E+02				
2.21 31-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	ug/l		7.1 E-01				
3,3'-dichlorobenzidine	lbs/day		1.4 E-01				
40.00.00	ug/l		2.5 E+03				
1,2-dichloroethane	lbs/day		4.7 E+02				
44.11.11.41.1	ug/l		7.9 E+01				
1,1-dichloroethylene	lbs/day		1.5 E+01				
D' 11 1 4	ug/l		5.5 E+02				
Dichlorobromomethane	lbs/day		1.0 E+02				
D111 4	ug/l		4.0 E+04				
Dichloromethane	lbs/day		7.6 E+03				
40.11.11	ug/l		7.8 E+02				
1,3-dichloropropene	lbs/day		1.5 E+02				
D	ug/l		3.5 E-03				
<u>Dieldrin</u>	lbs/day		6.7 E-04				
	ug/l		2.3 E+02				
2,4-dinitrotoluene	lbs/day		4.4 E+01				
10 11 11 1	ug/l		1.4 E+01				
1,2-diphenylhydrazine	lbs/day		2.7 E+00				
TT 1 /1 10	ug/l		1.1 E+04				
Halomethanes ¹⁰	lbs/day		2.2 E+03				
<u>Heptachlor</u>	ug/l		4.4 E-03				
	lbs/day		8.4 E-04				
	ug/l		1.8 E-03				
Heptachlor Epoxide	lbs/day		3.4 E-04				
	ug/l		1.8 E-02				
Hexachlorobenzene	lbs/day		3.5 E-03				
Hexachlorobutadiene	ug/l		1.2 E+03				

		Performance Goals						
Constituent	Units	Max	Avg	Avg	Instan	6 Month		
		Daily	Monthly	Weekly	Min	Max	Median	
	lbs/day		2.4 E+02					
Hexachloroethane	ug/l		2.2 E+02					
	lbs/day		4.2 E+01					
Isophorone	ug/l		6.4 E+04					
1	lbs/day		1.2 E+04					
N-nitrosodimethylamine	ug/l		6.4 E+02					
14 mirosoumentylamine	lbs/day		1.2 E+02					
N-nitrosodi-N-	ug/l		3.3 E+01					
propylamine	lbs/day		6.4 E+00					
N-nitrosodiphenylamine	ug/l		2.2 E+02					
N-muosodiphenyiamine	lbs/day		4.2 E+01					
DATE: 11	ug/l		7.7 E-01					
PAHs 11	lbs/day		1.5 E-01					
p.cp. 12	ug/l		1.7 E-03					
PCBs ¹²	lbs/day		3.2 E-04					
TCDD agriculants 13	ug/l		3.4 E-07					
TCDD equivalents ¹³	lbs/day		6.6 E-08					
1,1,2,2-	ug/l		2.0 E+02					
tetrachloroethane	lbs/day		3.9 E+01					
TD 4 11 41 1	ug/l		1.8 E+02					
<u>Tetrachloroethylene</u>	lbs/day		3.4 E+01					
	ug/l		1.8 E-02					
<u>Toxaphene</u>	lbs/day		3.5 E-03					
Trichloroethylene	ug/l		2.4 E+03					
	lbs/day		4.5 E+02					
1,1,2-trichloroethane	ug/l		8.3 E+02					
	lbs/day		1.6 E+02					
	ug/l		2.6 E+01					
2,4,6-trichlorophenol	lbs/day		4.9 E+00					
TH. 1011 1-	ug/l		3.2 E+03					
Vinyl Chloride	lbs/day		6.1 E+02					

51. The following paragraph has been added below Table 8. Performance Goals based on California Ocean Plan 2001 in Section IV.E Performance Goals on page F-25 of the Fact Sheet:

Performance goals serve to maintain existing treatment levels and effluent quality and supports State and federal antidegradation policies. Additionally, performance goals provide all interested parties with information regarding the expected levels of pollutants in the discharge that should not be exceeded in order to maintain the water

quality objectives established in the Ocean Plan. Performance goals are not limitations or standards for the regulation of the discharge. Effluent concentrations above the performance goals will not be considered as violations of the permit but serve as red flags that indicate water quality concerns. Repeated red flags may prompt the Regional Board to reopen and amend the permit to replace performance goals for constituents of concern with effluent limitations, or the Regional Board may coordinate such actions with the next permit renewal.

52. The following corrections to the first paragraph under Section VI.C Whole Effluent Testing Requirements on page F-29 of the Fact Sheet have been made:

The Discharger shall conduct acute and chronic toxicity testing on 24-hour composite effluent samples collected at Effluent Monitoring Station M-003, as defined in Section II of the MRP (Attachment E), on a monthly frequency. <u>Acute and chronic toxicity are required to be monitored semiannually and quarterly, respectively.</u>

53. The following corrections to Section VI.D.1 Surf Zone Water Quality Monitoring on page F-30 of the Fact Sheet have been made:

To assess bacteriological conditions in areas used for body contact activities and to assess aesthetic conditions for general recreational uses, Monitoring and Reporting Program (MRP) No. R9-2005-0136 requires that total and fecal coliform and enterococcus bacteria be monitored at a minimum frequency of once per week on an annual basis at six five surf zone locations. Recognizing that significant water-contact recreation, such as surfing and scuba diving, occurs year-round in ocean waters that may be impacted by the discharge from the OOO, the Regional Board adopted previously adopted Addendum No. 2 to Order No. 2000-011 which increased the surf zone monitoring frequency to weekly year-round from the previous minimum frequency of once per week from May 1 through October 31 and once every other week from November 1 through April 30 of each year.

In correspondence dated October 6, 2003, County of San Diego Department of Environmental Health (DEH) recommends using its "Standard Operating Procedures (SOP) for the Collection of Water Samples for Bacterial Analysis from Ocean and Bay Receiving Waters" as the sampling protocol at surf zone monitoring stations to reflect conditions during all critical environmental periods and be most protective of public health. The SOP specifies the time of day and depth for water sampling to reduce the effects of bacterial die-off in determining the actual bacterial densities that may be encountered by beach users. The SOP would also make sampling procedures consistent at sampling stations along the San Diego County coastline to facilitate data comparison.

For the period of July 2001 through August of 2004, samples collected <u>at</u> five surf zone stations have at times showed elevated bacterial levels that exceeded water quality objectives of the Ocean Plan for total and fecal coliform and exceeded recommended

levels for enterococcus. Surf zone monitoring station S-1, located at the mouth of the Buena Vista Lagoon south of the OOO, have frequently had elevated bacteria levels that may be due to outward flow from the lagoon. Order No. R9-2005-0136 suspends monitoring at station S1 and adds monitoring at two surf zone stations located 8,000 feet and 10,000 feet south of the OOO.

Order and MRP No. R9-2005-0136 retain the requirements of Order No. 2000-011 for surf zone water quality monitoring with the following modifications: and requires a sampling procedure for surf zone stations in accordance with County of San Diego DEH Standard Operating Procedures.

- a. Increases the overall sampling frequency from at surf zone stations.
- b. Removes one surf zone station and adds two new surf zone stations.
- c. Requires a sampling procedure for surf zone stations in accordance with County of San Diego DEH Standard.
- 54. The following corrections to Section VI.D.2 Near Shore Water Quality Monitoring on page F-31 of the Fact Sheet have been made:

To assess bacteriological conditions in areas used for body contact activities and where shellfish and/or kelp may be harvested, and to assess aesthetic conditions for general boating and recreational uses, MRP No. R9-2005-0136 establishes monitoring at six five near shore locations (3,000 feet seaward MLLW) for total and fecal coliform and enterococcus bacteria in surface samples on a year-round, monthly basis. These stations are located at the 30-foot depth contours opposite the surf zone stations. Enterococcus monitoring may be suspended in accordance with Endnote 11 of Appendix E: Monitoring and Reporting Program. Monitoring at one near shore station monitored under Order No. 2000-011 has been suspended and two stations have been added.

For the sample period of July 2001 through August of 2004, samples collected at near shore station N2 have at times exceeded the recommended 6-month geometric mean level for enterococcus but this may be due to the less sensitive analytical method used by the Discharger at times to measure enterococcus levels. Most other sample results were below the method detection limit for the period.

MRP No. R9-2005-0101 alters the sampling frequency and monitoring stations from Order No. 2000-011, otherwise, Order and MRP No. R9-2005-0136 retain the requirements of Order No. 2000-011 for near shore water quality monitoring.

55. The following correction to Section VI.D.3 Offshore Water Quality Monitoring on page F-32 of the Fact Sheet have been made:

MRP No. R9-2005-0136 alters the sampling frequency and monitoring stations from Order No. 2000-011, otherwise, Order and MRP No. R9-2005-0136 retain the requirements of

Order No. 2000-011 for offshore water quality monitoring.

56. The following correction to first paragraph under Section VI.E.1 Benthic Monitoring on page F-32 of the Fact Sheet has been made:

To assess the status of the benthic community and to evaluate the physical and chemical quality of sediments in the receiving water, Order No. R9-2005-0136 requires the following monitoring during first and third years year 4 of the Order.

57. The following correction to Section VI.E.5 Intensive Monitoring on page F-34 of the Fact Sheet has been made:

The Discharger shall perform the intensive monitoring as described by MRP No. R9-2005-0136 for <u>years 2 and 4 year 4</u> of the Order and participate in the Southern California Coastal Water Research Project (SCCWRP) Bight Study in year 5 of this Order.

- 58. Sections VI.E.6, VI.E., VI.E. regarding Plume Tracking, Determination of Compliance With Water Quality Objectives, and Urban Runoff Diversions, respectively, on page F-34 of Attachment F–Fact Sheet have been deleted.
- 59. Section VII.B.2.g regarding Pretreatment Program requirements on page F-36 of the Fact Sheet has been replaced with the following:

Pretreatment requirements established in Order No. 2000-011 are retained by this Order.

- 60. Sections VII.B.2.g, VII.B.2.h, VII.B.2.i regarding special studies for Urban Runoff Diversion Program, Plume Tracking, and Determination of Compliance With Water Quality Objectives, respectively, on page F-36 of Attachment F–Fact Sheet have been deleted.
- 61. The following changes to Section VI.E.1 *Benthic Monitoring* on pages F-28 and F-29 of Attachment F have been made:
- 62. The following corrections have been made to the second paragraph under Section VIII.B Written Comments on Page F-39:

To be fully responded to by staff and considered by the Regional Water Board, written comments should be received at the Regional Water Board offices by 5:00 p.m. on <u>June 1 July 27</u>, 2005.

63. The following corrections have been made to Section VIII.C Public Hearing on page F-39:

The Regional Water Board will hold a public hearing on the tentative WDRs during its regular Board meeting on the following date and time and at the following location:

Date: June 8 August 10, 2005

Time: 9:00 am

Location: Regional Water Quality Control Board, San Diego

9174 Sky Park Court Suite 100

San Diego, CA 92123